

# TVR-1604c-1T

## TruVision™ DVR 16c, HD-TVI Hybrid 4 channel compact recorder, 1TB

### Why the TVR 16?


The TVR 16 recorder series offers a full-featured, flexible hybrid recording solution that is ideal for (gradually) migrating an old analog video system to a modern high-resolution video system.

The TVR-1604c is a cost-effective recorder capable of recording up to 4 cameras.

As a true hybrid recorder, the TVR 16 can be used with analog, HD-TVI and IP cameras.

The recorder also supports HD-CVI (up to 4 MP) and HD-AHD (up to 5 MP) cameras.

This hybrid recorder is uniquely qualified to upgrade existing analog installations, offering a competitive, feature-rich and practical solution for the market of HD analog, standard analog and hybrid recorders.



### Open technology with powerful encoding

Using the open HD-TVI technology, TVR 1604c can connect to any HD-TVI camera up to 5 MP over existing coax cable.

As well as HD-TVI, TVR 16 also connects standard analog cameras and allows you to reuse existing analog cameras that do not yet need to be replaced/upgraded.

Finally, TVR 16 is capable of connecting all of its channels on IP cameras (up to 4K (8 MP)), making this is a true HD Hybrid series. The TVR 16 can use H.264 or H.265 encoding for analog, HD-TVI and IP cameras.

HD-CVI and HD-AHD cameras are supported in H.264 encoding.

### Unique intrusion integration

TVR 16 offers free integration with IP intrusion panels (Carrier) for video verification of (alarm) events. Alarm and arming/disarming events are sent from the intrusion panel to the recorder and can trigger actions in the recorder (recording, output control, PTZ control, email) and/or send notifications to TVRMobile or TruVision Navigator. The communication between recorder and panel is also monitored.

### Applications

The TVR 16 is suited for upgrading small sized analog video systems in (commercial) applications (residential, small offices, small shops) where high quality video is important without expensive cable costs.

### Details

- Linux embedded Plug and Play configuration
- Supports standard analog, HD-TVI, HD-AHD, HD-CVI and IP technology
- Up to 4 analog cameras or up to 4 IP cameras (when disabling all analog channels)
- Up to 5 MP HD-TVI camera support
- Up to 8 MP (4K) IP camera support
- Support for ONVIF Profile S IP cameras
- Over-the-coax control for TruVision fixed/PTZ HD-TVI cameras
- Use existing coax cabling for HD-TVI, HD-AHD and HD-CVI cameras
- Real time Full HD recording
- Supports dual stream recording on all channels
- Up to 2 TB internal storage
- Reverse video playback
- USB video export
- Start-up wizard for quick and easy installation
- HDMI, VGA and BNC video (event only) outputs
- V-stream support
- Front panel controls
- Operations through OSD/browser/software
- Integration of Aritech IP intrusion panels via SIA/XSIA reporting
- TruVision Navigator license-free client/host or standalone application
- TVRmobile app for iOS and Android
- IP Keypad support

# TVR-1604c-1T

## TruVision™ DVR 16c, HD-TVI Hybrid 4 channel compact recorder, 1TB

### Technical specifications

#### General

Operating system	Embedded Linux
Rack mountable	No

#### Video/audio input

Camera channels	4
Analog camera channels	4
IP camera channels	4 (with all analog channels disabled)
Max. bandwidth per channel	Analog: Up to 8 Mbps (main stream)/Up to 3 Mbps (sub stream) IP: follow capacity of IP camera but will not exceed 16 Mbps
Camera bandwidth	96 Mbps (combined in/out)
Audio compression	G.711
Max. analog audio In	4-ch, RCA (2.0 Vp-p, 1 kOhm)
Supported video compression standards	H.264, H.265
Supported video streaming standards	Onvif

#### Local viewing

HDMI output	1
HDMI version	1.4
VGA output	1
BNC output	1
Max. local output resolution	Full HD 1080p
Synchronous playback OSD (channels)	Up to 4 channels
Reverse playback OSD (channels)	Up to 1 channel

#### Remote viewing

Total available viewing bandwidth	Combined in and out bandwidth of 96 Mbps
Max. live viewing streams	128
Max. simultaneous playback web browser	Up to 4 channels
Browser compatibility	Google Chrome, Internet Explorer, Mozilla Firefox, Safari

#### Storage

Storage capacity	1 TB
SATA interfaces	1
Maximum recording resolution	4 K / 8 MPX (IP), 4 MPX (HD-CVI), 5 MPX (HD-AHD), 5 MPX (HD-TVI)
Recording modes	Alarm, Event, Manual, Time-lapse high, Time-lapse low
Dual stream recording (channels)	All channels

#### Networking

Network interface cards (NIC)	1
NIC type	RJ-45 10/100 Mbps self-adaptive Ethernet interface
DNS support	DDNS, ezDDNS, No-IP
HTTPS support	Yes

#### External interfaces

USB interface back	1
USB interface front	1
Serial interface	RS-232, RS-485
Alarm inputs	4
Alarm outputs	1
Max. analog audio outputs	1

#### Electrical

Power supply value	12 VDC (external PSU included)
Power consumption without HDD (W)	Less than 15W

#### Physical

Physical dimensions	315 x 242 x 45 mm (W x D x H)
Colour	Black

#### Environmental

Operating temperature	-10 to +55°C (14°F to 131°F)
Relative humidity	10 to 90%

#### Standards & regulation

Compliance	CE, REACH, RoHS, UL
------------	---------------------



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 27 August 2021 - 17:08